

EASY LEAD R

**DON'T GET CAUGHT BY
THEFT AND VANDALISM**

EASY LEAD R has:

- 20 year + life expectancy
- Is easy to install
- Is light and needs no additional sealants or tapes
- High performance adhesive for a permanent bond

**NO
RE SALE
VALUE**

TYPICAL APPLICATION:

Steps Valleys
Abutments
Saddles

Windows and Rooflights
Chimneys
Soakers

Valleys and Gutters
Dormers

Meir Roofing and Insulation Supplies

Unit C1, M62 trading Estate, Larsen Road, Goole, East Yorkshire, DN14 6XF

Tel: 01405 780 444 - 01752 559036 Fax: 01405 780 445

web: www.meir-roofing.co.uk - mail: sales@meir-roofing.co.uk

EASY LEAD R

NO RE SALE VALUE

EasyLead R is aluminium based, high performance, low cost flashing. It is used as a replacement of traditional lead in flat and pitched roof applications.

EasyLead R is made of sheet aluminium with a protective anti-corrosion coating and a high performance butyl adhesive on the underside.

EasyLead R doesn't require any special tools for installation. It can be cut with a knife or scissors.

KEY FEATURES OF EASYLEAD R

THEFT AND VANDALISM ARE ELIMINATED DUE TO EASYLEAD R HAVING NO RE-SALE VALUE!

Cost effective alternative to traditional lead

- Waterproof
- Durable
- Malleable
- Easy to install
- Easily Cut
- Easily Repaired
- Extremely Lightweight

TYPICAL APPLICATION

- Abutments
- Chimneys
- Dormers
- Saddles
- Soakers
- Stepped
- Valleys
- Windows and Rooflights
- Valleys and Gutters

EasyLead R has a unique corrugated pattern so it is easy to form and to adapt to various surfaces; this malleability ensures the permanent water tightness of the product and an attractive appearance every time.

EasyLead R provides a permanent bond to brickwork, roof tiles and most popular construction materials.

INSTALLATION

EasyLead R is easily installed using a knife or scissors to cut. **EasyLead R** can be Installed and worked in any direction using a mallet, roller or by hand.

Determine the final installation position of **EasyLead R** maintaining the release film until achieved, once satisfied remove the release film and dress the material to the brickwork or applicable surface. Joints should have a minimum overlap of 100 mm.

To achieve a permanent adhesion of **EasyLead R** the building material surface has to be clean and dry.

A bituminous primer is recommended for unstable material surfaces.

PRODUCT DATA

Roll width/mm	150	300	450
Roll weight/kilos	1.5	3	4.5
Roll length/mtrs	5mtr	5mtr	5mtr

TECHNICAL DATA

Colour: Grey
Surface finish: Corrugated
Temp. Resistance: -40°C / +90°C
Min. working temp: +5°C
Life expectancy: Minimum 20 yrs
Resistant against: corrosion and UV degradation: Yes

Meir Roofing and Insulation Supplies

Unit C1, M62 trading Estate, Larsen Road, Goole, East Yorkshire, DN14 6XF

Tel: 01405 780 444 - 01752 559036 Fax: 01405 780 445

web: www.meir-roofing.co.uk - mail: sales@meir-roofing.co.uk